

# Mayfield Concept Plan

Annual Noise Verification Review

# Mayfield Concept Plan

## Annual Noise Verification Review

Client: Port of Newcastle Operations Pty Ltd

ABN: 97 539 122 070

### Prepared by

**AECOM Australia Pty Ltd**

Level 21, 420 George Street, Sydney NSW 2000, PO Box Q410, QVB Post Office NSW 1230, Australia  
T +61 2 8934 0000 F +61 2 8934 0001 www.aecom.com  
ABN 20 093 846 925

20-Dec-2016

Job No.: 60518192

AECOM in Australia and New Zealand is certified to ISO9001, ISO14001 AS/NZS4801 and OHSAS18001.

© AECOM Australia Pty Ltd (AECOM). All rights reserved.

AECOM has prepared this document for the sole use of the Client and for a specific purpose, each as expressly stated in the document. No other party should rely on this document without the prior written consent of AECOM. AECOM undertakes no duty, nor accepts any responsibility, to any third party who may rely upon or use this document. This document has been prepared based on the Client's description of its requirements and AECOM's experience, having regard to assumptions that AECOM can reasonably be expected to make in accordance with sound professional principles. AECOM may also have relied upon information provided by the Client and other third parties to prepare this document, some of which may not have been verified. Subject to the above conditions, this document may be transmitted, reproduced or disseminated only in its entirety.

## Quality Information

Document Mayfield Concept Plan




Ref 60518192-RPNV-03\_C

Date 20-Dec-2016

Prepared by Angus Leslie

Reviewed by Patrick Martinez

### Revision History

Rev	Revision Date	Details	Authorised	
			Name/Position	Signature
A	19-Dec-2016	Draft for review	Patrick Martinez Associate Director - Acoustics	
B	19-Dec-2016	Final issue	Patrick Martinez Associate Director - Acoustics	
C	20-Dec-2016	Final issue	Patrick Martinez Associate Director - Acoustics	

## Table of Contents

Abbreviations	5
Glossary	5
Document References	5
1.0 Introduction	6
2.0 Objectives	6
3.0 Individual Project Review and Results	9
3.1 Approach	9
3.2 Individual project predicted operational noise levels	9
3.2.1 Project 1 – Stolthaven Bulk Liquids Fuel Storage Facility (Stolthaven)	9
4.0 Overall Mayfield Concept Plan Noise Levels	11
4.1 Approach	11
5.0 Discussion and Recommendations	11
6.0 Conclusion	12
Appendix A	
Acoustic Terminology	A

## Abbreviations

AS	Australian Standard
AS/NZS	Australian/New Zealand Standard
CENMT	Cumulative Environmental Noise Management Tool
CoA	The Minister for Planning's Conditions of Approval
DGM	Digital ground model
DP&E	Department of Planning and Environment
EA	Environmental Assessment
EPA	NSW Environment Protection Authority
EPL	Environment Protection Licence
GIS	Geographic Information System
INP	NSW Industrial Noise Policy
MCP	Mayfield Concept Plan
NVMP	Noise Verification Monitoring Plan
OEMP	Operation Environmental Management Plan
ONMP	Operation Noise Management Plan
PON	Port of Newcastle Operations Pty Ltd
SoundPLAN	SoundPLAN noise modelling software

## Glossary

Project	An individual development within the MCP and falls part of the MCP approval.
Noise Quota	The noise goals for an individual project site within the MCP.

## Document References

Document	Reference Document	Revision
Mayfield Concept Plan Noise Verification Monitoring Plan	60437494-RPNV-01_C	Revision C - 15 October 2015
Mayfield Concept Plan Cumulative Noise Modelling – User Guide	60289391.RPT01.01 MCP Noise User Guide	Revision 01 – 15 July 2015
Stolthaven Bulk Liquids Fuel Storage Facility, Mayfield Operational Noise Compliance Assessment	60326869-RPNV-04_C	Revision A – 20 December 2016

## 1.0 Introduction

A concept approval (Application 09\_0096) under Section 75O of the EP&A Act was granted by the Minister for Planning on 16 July 2012 for the Mayfield Concept Plan (MCP) site (latest modification 12 December 2014). The MCP conditions of approval (CoA) require the consideration of the cumulative noise impacts from existing and future projects. Port of Newcastle Operations Pty Ltd (PON) has developed a Cumulative Environmental Noise Management Tool (CENMT) to assess and manage existing and future noise emission from individual project and cumulative noise impacts from the MCP area.

PON has developed a Noise Verification Monitoring Plan (NVMP) for the MCP, in order to monitor and review both individual project noise emissions against the issued noise quota, and to then review the cumulative of operational noise impacts from the overall MCP area.

AECOM Australia Pty Ltd (AECOM) has been commissioned by PON to undertake this year's (2016) annual noise verification review of the MCP.

This verification review has been prepared to satisfying the MCP concept approval acoustic requirements, specifically condition **2.20 Noise Verification Monitoring Program**, which requires monitoring and reporting operational noise emissions.

The MCP CoA noise goals are limited to the assessment of noise emissions over NSW Environmental Protection Authority (EPA) NSW Industrial Noise Policy (INP) *amenity* periods. For other regulatory acoustic requirements, e.g. EPA Environment Protection Licence (EPL) noise limits, noise compliance assessments for the individual projects will incorporate these where required in their approval conditions.

Noise emissions as part of the short term 15-minute period INP intrusive noise assessment, sleep disturbance impacts are address at an individual project level, and currently do not form part of PON's noise management of the MCP area.

As per Section 1.6 of the MCP approval, noise emissions associated with the berths, berthing or harbour operations (i.e. shipping activities) are excluded from contributing to the overall MCP noise emissions.

As per Section 1.14 of the MCP approval, Mayfield No. 4 Berth is excluded from the MCP area as it operates under an existing approval (Consent Condition DA-293-08-00 MOD 9, dated 29 August 2013) and has noise limit requirements as part of this consent condition.

Acoustic terminology used in this report is included in **Appendix A**.

## 2.0 Objectives

As outlined in the MCP NVMP, the individual project tenants are responsible for undertaking the verification noise assessments against the PON issued noise quotas.

PON is then responsible for collating and reviewing the individual project's noise verification and compliance assessments. In addition, PON is responsible for combining the outputs from these compliance assessments to determine the overall noise emission from the entire MCP site.


The MCP CoA requires that the overall operational noise levels associated with the MCP '*must comply with the amenity noise goals at sensitive residential receivers*'. The amenity noise goals applicable to the entire MCP are presented in **Table 1**.

**Table 1** Mayfield Concept Plan amenity noise goals at nearby residences

Noise Verification Location	Project Specific Noise Goals (dB(A)) $L_{Aeq(Period)}$		
	Day (7.00 am to 6.00 pm)	Evening (6.00 pm to 10.00 pm)	Night (10.00 pm to 7.00 am)
A - 1 Arthur Street, Mayfield (Urban)	60	49	43
B - 2 Crebert Street, Mayfield (Urban)	60	50	43
C – 32 Elizabeth Street, Carrington (Urban)	57	44	45
D – Stockton (Suburban)	55	37	37

The above noise goals apply under winds of up to three metres per second (measured at 10 metres above ground level) and Pasquill stability class from A to F.

The locations of the residential noise verification locations are presented in **Figure 1**.



**Legend**

- Noise assessment location
- Stolthaven Bulk Fuel Terminal
- Northern access road
- Mayfield Berth 4
- Mayfield Concept Plan Boundary

A-1 Arthur St, Mayfield

B-2 Crebert St, Mayfield

C-32 Elizabeth St, Carrington

D-186 Fullerton Rd, Stockton

© Land and Property Information 2015

Mayfield Concept Plan - Annual Noise Verification Review  
Individual project site locations, MCP area and noise assessment locations

Dec 2016  
60326869




Figure 1



## 3.0 Individual Project Review and Results

### 3.1 Approach

As per the requirements of the MCP NVMP, individual projects have undertaken annual noise verification assessments (through the use of the *SoundPLAN Verification Model*) and these were provided to PON to undertake the annual noise verification review of the MCP.

These noise verification assessments address the operational noise emissions against the project's noise quota levels that were issued and approved by PON. These individual project noise compliance assessments have been reviewed by PON for adequacy against the requirements of the *Mayfield Concept Plan Cumulative Noise Modelling – User Guide (Modelling User Guide)*.

All projects have been modelled using the *SoundPLAN Verification Model* issued for the 2016 individual project noise verification assessments. The noise emissions from all projects are based upon 'reasonable' worst case operational scenarios that occurred over the 2016 review period, in accordance with the approach for reviewing the performance of noise emissions from industrial facilities in NSW, as per Chapter 11 of the EPA INP.

### 3.2 Individual project predicted operational noise levels

PON has developed and implemented a Cumulative Environmental Noise Management Tool (CENMT) to manage individual MCP's project noise emission requirements.

**Table 2** presents a summary of the predicted noise emission levels at each of the assessment receiver locations for each of the approved projects within the MCP. The results presented in **Table 2** indicate the projects' noise emission performance against the PON issued noise quotas. These predicted noise levels are for the highest noise impacts under all assessment meteorological conditions.

#### 3.2.1 Project 1 – Stolthaven Bulk Liquids Fuel Storage Facility (Stolthaven)

During this year's (2016) annual noise verification review of the MCP, the Stolthaven Bulk Liquids Fuel Storage Facility (Stolthaven) is the only approved operational project within the MCP. It is noted that project specific noise quotas were not issued as part of the Stolthaven's current approval (SSD 6664 MOD 1), since the CENMT was under development at the time that this project received formal approval. Stolthaven submitted a revised application (SSD 7056 (Stage 3)) for an operating approval which will include their current operations. The revised Stolthaven application has been approved and noise quotas have been allocated by PON, however existing approval limits remain valid.

For the purposes of assessing Stolthaven's noise emission against the requirements of the MCP; this project will be assessed against the overall MCP amenity noise goals only, refer to **Table 1**. This is deemed appropriate for the 2016 noise verification review, as the Stolthaven is the only approved project within the MCP.

Table 2 Individual project predicted noise emission verification review

Project No. / Description	Noise Verification Location	Projects Compliance Noise Emission Review								
		Compliance Noise Level, L <sub>Aeq, period</sub> dB(A)			MCP Noise Quota, L <sub>Aeq, period</sub> dB(A)			Compliance		
		Day	Evening	Night	Day	Evening	Night	Day	Evening	Night
<b>Project 1 Stolthaven</b>	A	<b>26</b>	<b>29</b>	<b>26</b>	- <sup>1</sup>	- <sup>1</sup>	- <sup>1</sup>	N/A	N/A	N/A
	B	<b>34</b>	<b>37</b>	<b>35</b>	- <sup>1</sup>	- <sup>1</sup>	- <sup>1</sup>	N/A	N/A	N/A
	C	<b>16</b>	<b>23</b>	<b>17</b>	- <sup>1</sup>	- <sup>1</sup>	- <sup>1</sup>	N/A	N/A	N/A
	D	<b>16</b>	<b>23</b>	<b>17</b>	- <sup>1</sup>	- <sup>1</sup>	- <sup>1</sup>	N/A	N/A	N/A

Notes:

1. Project specific noise quota was not issued as part of the SSD 6664 MOD 1 approval, refer to Section 3.2.1.

## 4.0 Overall Mayfield Concept Plan Noise Levels

### 4.1 Approach

PON has reviewed the noise verification assessment of all the projects within the MCP, and has collated the 2016 operational compliance noise levels. All individual project compliance results have been combined into the MCP *SoundPLAN Master Model*, which includes all individual projects, to determine the cumulative impacts from approved projects within the MCP.

**Table 3** presents a summary of the cumulative compliance noise levels from all approved projects within the MCP.

**Table 3 Cumulative compliance noise verification review**

Noise Verification Location	Cumulative Compliance Noise Emission Review								
	Compliance Noise Level			MCP Overall Noise Goals			Compliance		
	L <sub>Aeq</sub> (Period)			L <sub>Aeq</sub> (Period)					
	Day	Evening	Night	Day	Evening	Night	Day	Evening	Night
A	26	29	26	60	49	43	Yes	Yes	Yes
B	34	37	35	60	50	43	Yes	Yes	Yes
C	16	23	17	57	44	45	Yes	Yes	Yes
D	16	23	17	55	37	37	Yes	Yes	Yes

## 5.0 Discussion and Recommendations

During this year's (2016) annual noise verification review of the MCP, there was only one approved operational project with the MCP. Noise emissions from Stolthaven have been assessed against the MCP overall amenity noise goals and compliance has been found at all receiver locations, during all assessment periods under all prevailing meteorological conditions. As such, there are no recommendations as a result of the 2016 noise verification review.

AECOM understands that no noise complaints were receiver directly attributable to operations within the MCP over 2016.

## 6.0 Conclusion

Port of Newcastle Operations Pty Ltd (PON) has commissioned AECOM Australia Pty Ltd (AECOM) to carry out the Annual Noise Verification Review for the Mayfield Concept Plan (MCP), Mayfield, NSW.

PON has developed and implemented a Noise Verification Monitoring Plan (NVMP) for the MCP, in order to monitor and review individual projects noise emissions against the noise quota issued by PON and then collate and review the cumulative of all operational noise impacts from the overall MCP area.

Currently there is only one approved operational project with the MCP. Noise emissions from this project (i.e. Stolthaven Bulk Liquids Fuel Storage Facility (Stolthaven)) have been assessed against the MCP amenity noise goals to determine the overall impact from approved operations within the MCP.

Compliance has been found at all receiver locations, during all assessment periods under all prevailing meteorological conditions.



# Appendix A

## Acoustic Terminology

## Appendix A Acoustic Terminology

The following is a brief description of acoustic terminology that may have been used in this report.

<i>Sound power level</i>	The total sound emitted by a source																						
<i>Sound pressure level</i>	The amount of sound at a specified point																						
<i>Decibel [dB]</i>	The measurement unit of sound																						
<i>A Weighted decibels [dB(A)]</i>	The A weighting is a frequency filter applied to measured noise levels to represent how humans hear sounds. The A-weighting filter emphasises frequencies in the speech range (between 1kHz and 4 kHz) which the human ear is most sensitive to, and places less emphasis on low frequencies at which the human ear is not so sensitive. When an overall sound level is A-weighted it is expressed in units of dB(A).																						
<i>Decibel scale</i>	<p>The decibel scale is logarithmic in order to produce a better representation of the response of the human ear. A 3 dB increase in the sound pressure level corresponds to a doubling in the sound energy. A 10 dB increase in the sound pressure level corresponds to a perceived doubling in volume. Examples of decibel levels of common sounds are as follows:</p> <table> <tr> <td>0dB(A)</td> <td>Threshold of human hearing</td> </tr> <tr> <td>30dB(A)</td> <td>A quiet country park</td> </tr> <tr> <td>40dB(A)</td> <td>Whisper in a library</td> </tr> <tr> <td>50dB(A)</td> <td>Open office space</td> </tr> <tr> <td>70dB(A)</td> <td>Inside a car on a freeway</td> </tr> <tr> <td>80dB(A)</td> <td>Outboard motor</td> </tr> <tr> <td>90dB(A)</td> <td>Heavy truck pass-by</td> </tr> <tr> <td>100dB(A)</td> <td>Jackhammer/Subway train</td> </tr> <tr> <td>110 dB(A)</td> <td>Rock Concert</td> </tr> <tr> <td>115dB(A)</td> <td>Limit of sound permitted in industry</td> </tr> <tr> <td>120dB(A)</td> <td>747 take off at 250 metres</td> </tr> </table>	0dB(A)	Threshold of human hearing	30dB(A)	A quiet country park	40dB(A)	Whisper in a library	50dB(A)	Open office space	70dB(A)	Inside a car on a freeway	80dB(A)	Outboard motor	90dB(A)	Heavy truck pass-by	100dB(A)	Jackhammer/Subway train	110 dB(A)	Rock Concert	115dB(A)	Limit of sound permitted in industry	120dB(A)	747 take off at 250 metres
0dB(A)	Threshold of human hearing																						
30dB(A)	A quiet country park																						
40dB(A)	Whisper in a library																						
50dB(A)	Open office space																						
70dB(A)	Inside a car on a freeway																						
80dB(A)	Outboard motor																						
90dB(A)	Heavy truck pass-by																						
100dB(A)	Jackhammer/Subway train																						
110 dB(A)	Rock Concert																						
115dB(A)	Limit of sound permitted in industry																						
120dB(A)	747 take off at 250 metres																						
<i>Frequency [f]</i>	The repetition rate of the cycle measured in Hertz (Hz). The frequency corresponds to the pitch of the sound. A high frequency corresponds to a high pitched sound and a low frequency to a low pitched sound.																						
<i>Equivalent continuous sound level [L<sub>eq</sub>]</i>	The constant sound level which, when occurring over the same period of time, would result in the receiver experiencing the same amount of sound energy.																						
<i>L<sub>max</sub></i>	The maximum sound pressure level measured over the measurement period																						
<i>L<sub>min</sub></i>	The minimum sound pressure level measured over the measurement period																						
<i>L<sub>10</sub></i>	The sound pressure level exceeded for 10% of the measurement period. For 10% of the measurement period it was louder than the L <sub>10</sub> .																						

<i>L<sub>90</sub></i>	The sound pressure level exceeded for 90% of the measurement period. For 90% of the measurement period it was louder than the L <sub>90</sub> .
<i>Ambient noise</i>	The all-encompassing noise at a point composed of sound from all sources near and far.
<i>Background noise</i>	The underlying level of noise present in the ambient noise when extraneous noise (such as transient traffic and dogs barking) is removed. The L <sub>90</sub> sound pressure level is used to quantify background noise.
<i>Traffic noise</i>	The total noise resulting from road traffic. The L <sub>eq</sub> sound pressure level is used to quantify traffic noise.
<i>Day</i>	The period from 0700 to 1800 h Monday to Saturday and 0800 to 1800 h Sundays and Public Holidays.
<i>Evening</i>	The period from 1800 to 2200 h Monday to Sunday and Public Holidays.
<i>Night</i>	The period from 2200 to 0700 h Monday to Saturday and 2200 to 0800 h Sundays and Public Holidays.
<i>Assessment background level [ABL]</i>	The overall background level for each day, evening and night period for <b>each day</b> of the noise monitoring.
<i>Rating background level [RBL]</i>	The overall background level for each day, evening and night period for the <b>entire length</b> of noise monitoring.
<i>Weighted sound reduction index [R<sub>w</sub>]</i>	A single figure representation of the air-borne sound insulation of a partition based upon the R values for each frequency measured in a laboratory environment.

\*Definitions of a number of terms have been adapted from Australian Standard AS1633:1985 “Acoustics – Glossary of terms and related symbols”, the EPA’s NSW Industrial Noise Policy and the EPA’s Road Noise Policy.