

# **Mayfield Concept Plan Approval**

## **Quarterly Stormwater Monitoring Report**

September 2022 to November 2022 Date of sampling: NA Date Published: 31/1/2023

In accordance with Schedule 3 Condition 2.21 (d) of the Mayfield Concept Approval, PON has developed a Stormwater Management Strategy for the site.

To support the strategy PON conducts an ongoing site wide monitoring program to confirm that the site continues to meet the commitments and requirements of the Concept Plan Approval. Sampling is undertaken on a quarterly basis at the downstream extent of the site drainage infrastructure prior to discharge into the Eastern and Western drains. There are a total of six sampling locations. Please refer to Figure 1 below.

## Figure 1: Mayfield Site Water Quality Monitoring Locations





Analytes that are to be monitored at each sample location are detailed in Table 1 below.

#### Table 1: Analytes for Stormwater

| Analyte                            | Unit of Measure | Frequency | Sampling Method                   |
|------------------------------------|-----------------|-----------|-----------------------------------|
| Total suspended solids             | mg/L            | Quarterly | Grab sample during rainfall event |
| рН                                 | pH units        | Quarterly | Grab sample during rainfall event |
| Nitrogen (total)                   | ug/L            | Quarterly | Grab sample during rainfall event |
| Oil and grease                     | mg/L            | Quarterly | Grab sample during rainfall event |
| Phosphate                          | ug/L            | Quarterly | Grab sample during rainfall event |
| BOD                                | mg/L            | Quarterly | Grab sample during rainfall event |
| Dissolved oxygen                   | %               | Quarterly | Grab sample during rainfall event |
| Heavy metals (comprehensive suite) | ug/L            | Annually  | Grab sample during rainfall event |

Stormwater sampling is triggered by rainfall events of greater than 25mm rainfall in the preceding 24hr period. This is necessary to ensure there is sufficient volume of water continuing to flow into the drains to enable sample collection, given the open free-draining nature of the drains.

The September to November period experienced relatively low rainfall with no rainfall events exceeding the 25mm daily total necessary for sampling.

### Table 2: Rainfall Summary

|                            | Sep-22 | Oct-22 | Nov-22 |
|----------------------------|--------|--------|--------|
| Highest 24 Hour Total (mm) | 15     | 22.2   | 16.8   |
| Monthly Total (mm)         | 82.2   | 66.2   | 32.8   |

The largest daily total was 22.2mm in October, however this coincided with a 9am Saturday to 9am Sunday period when environmental staff are not available to inspect and attempt sampling.